



RCF12-50JFN

1/2" RADIAFLEX® RCF Cable



- RADIAFLEX® functions as a distributed antenna to provide communications in tunnels, mines and large building complexes and is the solution for any application in confined areas.
- Slots in the copper outer conductor allow a controlled portion of the internal RF energy to be radiated into the surrounding environment. Conversely, a signal transmitted near the cable will couple into the slots and be carried along the cable length.
- RADIAFLEX® is used for both one-way and two-way communication systems and because of its broadband capability, a single radiating cable can handle multiple communication systems simultaneously.
- This RADIAFLEX® radiating cable utilize a low-loss cellular polyethylene foam dielectric and a corrugated copper outer conductor which offers a combination of remarkable flexibility, high strength and excellent electrical performance.

Features / Benefits

- Broadband radiating cable supporting all wireless application between 75 MHz to 6000 MHz
- Ideally suited for application that require low bending radii
- Robust radiating cable operational under all enviromental conditions as e.g. harsh tunnels or mines

Technical Features

STRUCTURE

Cable Type	RCF
Size	1/2
Inner Conductor Material	Copper Clad Aluminum Wire
Outer Conductor Material	Corrugated Copper Tube
Jacket	JFN
Jacket Color	Standard Black, other colors on request
Jacket Description	Halogen free, non corrosive, flame retardant, low smoke, polyolefin
Slot Design	Milled (Two-Row)
Indication of Slot Alignment	None

MECHANICAL SPECIFICATION

Diameter Inner Conductor	4.8mm (0.19in)
Diameter Outer Conductor	13.8mm (0.54in)
Minimum Bending Radius	125mm (4.9in)
Cable Weight	0.22kg/m (0.15lb/ft)
Tensile Force	1,100N (247lb)
Recommended / Maximum Clamp Spacing	0.6m (2ft)
Minimum Distance to Wall	50mm (1.97in)



RCF12-50JFN

1/2" RADIAFLEX® RCF Cable

ELECTRICAL SPECIFICATION

Impedance	50 +/- 2 Ω							
Max. Operating Frequency	6,000 MHz							
Velocity	88 %							
Capacitance	76pF/m (23.2pF/ft)							
Inductance	0.19μH/m (0.058μH/ft)							
DC-resistance inner conductor	1.57Ω/km (0.48Ω/kft)							
DC-resistance outer conductor	3.48Ω/km (1.06Ω/kft)							
Stop bands	None							
Frequency Selection	600	900	1800/1900	2200	2400	2500	2700	6000

TESTING AND ENVIRONMENTAL

Operation Temperature	-40 - 85 °C (-40 - 185°F)
Installation Temperature	-25 - 60 °C (-13 - 140°F)
Storage Temperature	-70 - 85 °C (-94 - 185°F)
Compliance	Test methods for fire behaviour of cable : IEC 60754-1/-2 smoke emission: halogen free, non corrosive IEC 61034 low smoke IEC 60332-1 flame retardant

ATTENUATION AND COUPLING LOSS

Frequency, MHz	Longitudinal Loss, dB/100 m (dB/100 ft)	Coupling Loss 50%, dB	Coupling Loss 95%, dB
75	2.20 (0.67)	50	62
150	3.15 (0.96)	59	71
450	5.70 (1.74)	67	79
800	7.83 (2.39)	67	79
870	8.25 (2.51)	66	79
900	8.40 (2.56)	66	78
960	8.65 (2.64)	66	78
1800	13.1 (3.99)	68	80
1900	13.6 (4.15)	69	81
2000	14.0 (4.27)	72	84
2200	14.7 (4.48)	70	82
2400	15.3 (4.66)	70	82
2600	15.9 (4.85)	70	82
5000	24.8 (7.56)	75	87
5200	25.7 (7.83)	75	87
5800	27.6 (8.41)	75	87
6000	29.9 (8.81)	75	87

@ 20°C (68°F)

NOTES

- Coupling loss as well as longitudinal attenuation of RADIAFLEX® cables are measured by the free space method according to IEC 61196-4.
- Coupling loss values are average values of all three spatial orientations (radial, parallel and orthogonal) of dipole antenna.



RCF12-50JFN

1/2" RADIAFLEX® RCF Cable

- Coupling loss values are given with a tolerance of +10 dB and longitudinal loss values with a tolerance of +5%. Note: Measured values below nominal are better. They are not limited by any tolerance-range.
- As with any radiating cable, the performance in building or tunnel environments may deviate from figures based on free space method.