

**RAYA158-50JFNA**

1-5/8" RADIAFLEX® RAYA Cable, A-series



- RADIAFLEX® functions as a distributed antenna to provide communications in tunnels, mines and large building complexes and is the solution for any application in confined areas.
- Slots in the copper outer conductor allow a controlled portion of the internal RF energy to be radiated into the surrounding environment. Conversely, a signal transmitted near the cable will couple into the slots and be carried along the cable length.
- RADIAFLEX® is used for both one-way and two-way communication systems and because of its broadband capability, a single radiating cable can handle multiple communication systems simultaneously.
- This RADIAFLEX® radiating cable utilize a low-loss cellular polyethylene foam dielectric and a smooth copper outer conductor which offers a superior electrical performance together with good bending properties.

Features / Benefits

- Ultra wideband from 75 MHz to 2700 MHz
- Support of all commercial and mission critical wireless services between 75 and 2700 MHz
- Future proof: Supports frequency spectrum re-banding/re-farming
- Unconditionally 4G ready in all 3GPP bands
- Homogeneous (balanced) system loss over frequency
- Designed for a variety of in-tunnel applications

Technical Features**STRUCTURE**

Cable Type	RAY
Size	1-5/8
Inner Conductor Material	Corrugated Copper Tube
Outer Conductor Material	Overlapping Copper Foil
Jacket	JFN
Jacket Color	black
Jacket Description	Halogen free, non corrosive, flame and fire retardant, low smoke, polyolefin
Slot Design	Groups of slope slots at short intervals
Indication of Slot Alignment	Guides opposite to slots

MECHANICAL SPECIFICATION

Diameter Inner Conductor	17.6mm (0.69in)
Diameter Outer Conductor	44.2mm (1.74in)
Minimum Bending Radius	700mm (28in)
Cable Weight	1.01kg/m (0.68lb/ft)
Tensile Force	1,200N (270lb)
Recommended / Maximum Clamp Spacing	1.5m (5ft)
Minimum Distance to Wall	80mm (3.15in)

**RAYA158-50JFNA**

1-5/8" RADIAFLEX® RAYA Cable, A-series

ELECTRICAL SPECIFICATION

Impedance	50 +/- 2 Ω				
Max. Operating Frequency	2,700 MHz				
Velocity	90 %				
Capacitance	73pF/m (21.9pF/ft)				
Inductance	0.18 μ H/m (0.055 μ H/ft)				
DC-resistance inner conductor	1.62 Ω /km (0.49 Ω /kft)				
DC-resistance outer conductor	1.47 Ω /km (0.45 Ω /kft)				
Stop bands	No Stop bands				
Frequency Selection	600	900	1800/1900	2200	2400

TESTING AND ENVIRONMENTAL

Operation Temperature	-40 - 85 °C (-40 - 185°F)
Installation Temperature	-25 - 60 °C (-13 - 140°F)
Storage Temperature	-70 - 85 °C (-94 - 185°F)
Compliance	Test methods for fire behaviour of cable : IEC 60754-1/-2 smoke emission: halogen free, non corrosive IEC 61034 low smoke IEC 60332-1 flame retardant IEC 60332-3-24 fire retardant UL1666, ASTM E 662, NES711 and NES713

ATTENUATION AND COUPLING LOSS

Frequency, MHz	Longitudinal Loss, dB/100 m (dB/100 ft)	Coupling Loss 50%, dB	Coupling Loss 95%, dB
75	0,54 (0,16)	64 (68)	74 (77)
150	0,76 (0,23)	76 (80)	85 (90)
450	1,42 (0,43)	75 (79)	80 (84)
610	1,68 (0,51)	73 (77)	78 (82)
700	1,84 (0,56)	74 (76)	79 (81)
800	1,99 (0,60)	72 (75)	76 (79)
900	2,15 (0,66)	73 (77)	77 (82)
960	2,26 (0,69)	71 (75)	76 (79)
1700	3,30 (1,01)	66 (71)	72 (77)
1800	3,49 (1,06)	67 (69)	74 (77)
1900	3,69 (1,12)	67 (69)	73 (77)
2000	3,85 (1,17)	64 (68)	71 (75)
2100	4,08 (1,24)	64 (68)	70 (75)
2200	4,26 (1,30)	64 (68)	70 (74)
2300	4,54 (1,38)	62 (66)	68 (73)
2400	4,85 (1,48)	62 (66)	68 (72)
2500	5,23 (1,59)	61 (65)	67 (72)
2600	5,68 (1,73)	60 (64)	65 (70)
2700	6,62 (2,02)	59 (63)	66 (71)

@ 20°C (68°F)



RAYA158-50JFNA

1-5/8" RADIAFLEX® RAYA Cable, A-series

NOTES

- Coupling loss as well as longitudinal attenuation of RADIAFLEX® cables are measured by the free space method according to IEC 61196-4.
- Coupling loss values are measured with a radial (below 400 MHz) or orthogonal (above 400 MHz) orientated dipole antenna.
- The coupling loss values given in brackets are average values of all three spatial orientations (radial, parallel and orthogonal) of dipole antenna.
- Coupling loss values are given with a tolerance of +5 dB and longitudinal loss values with a tolerance of +5%. Note: Measured values below nominal are better. They are not limited by any tolerance-range.
- In case of a conflict of operational and stop band, please contact RFS for further assistance.
- As with any radiating cable, the performance in building or tunnel environments may deviate from figures based on free space method.